



## POWER ELECTRONICS CAPACITORS

27/08/2014

# CML13306AMJ3C

### RATING, GENERAL CHARACTERISTICS

Rated capacitance	Cn	33	μF
Capacitance tolerance		±5	%
Rated AC voltage (rms)	Urms	550	Vac
Rated AC voltage	UR	776	Vac
Recurrent peak voltage	UN	1100	V
Non recurrent peak voltage	Us	1925	V
Rated RMS current	Irms	65	A
Maximum dV/dt	dV/dt	40	V/μs
Repetitive peak current(max. peak current $\hat{i}$ -EN 61071)	Ipkr	1320	A
Non repetitive peak current(max. surge current $\hat{i}$ s-EN 61071)	Ipkn	3300	A
Equivalent series resistance	ESR(typ)	2	mΩ
Tangent of the loss angle tanδ (1kHz) (typ)	tgδ(typ)	0,0015	-
Tangent of the loss angle tanδ (1kHz) (max)	tgδ(max)	0,002	-
Self inductance	Ls	150	nH

### TEST DATA

A.C. Test voltage between terminals (50Hz, 3s)	Utt	1000	Vac
A.C. Test voltage between terminals and case(50Hz, 3s)	Utc	3500	Vac

### ENVIRONMENTAL CHARACTERISTICS

Max permissible case temperature	t°max	85	°C
Min permissible case temperature	t°min	-40	°C

### RELIABILITY

Max. expected number failures for 10 <sup>9</sup> components hours	FIT	300	
Expected life at URMS	Ln≥	100000	hours

### MECHANICAL CHARACTERISTICS

Dimensions	DXH	75X140	mm
Case material		Aluminium	
Fixing	Stud M12	16	mm
Plastic plate	UL-94 V0 , low smoke		
Approx weight		1000	gr
Terminals	Screw M10	20	mm
Maximum drawing torque		10	N/m
Mounting position		Any position without restriction	



**POWER ELECTRONICS CAPACITORS**

**27/08/2014**

**CML13306AMJ3C**

**RATING, GENERAL CHARACTERISTICS**

