

Rated Power, Qn kvar	Capacitance, 3x Cn, μF	Rated Current, Irms A	Dimensions, mm			Code
			W	D	H	
Rated voltage Urms = 230 VAC, f_n = 50Hz, Delta Connection, with internal discharge resistor⁽¹⁾						
2,5	3x 50	6,3	250	80	283	CMA32325
5	3x 100	12,5	250	80	283	CMA32350
Rated voltage Urms = 400 VAC, f_n = 50Hz, Delta Connection, with internal discharge resistor⁽¹⁾						
2,5	3x 16,6	3,6	250	80	283	CMA34025
5	3x 33,3	7,2	250	80	283	CMA34050
7,5	3x 50,0	10,8	250	80	283	CMA34075
10	3x 66,6	14,4	250	80	283	CMA34100
12,5	3x 83	18,1	250	80	283	CMA34125
Rated voltage Urms = 415 VAC, f_n = 50Hz, Delta Connection, with internal discharge resistor⁽¹⁾						
5	3x 30,8	7,0	250	80	283	CMA34105
10	3x 61,5	13,9	250	80	283	CMA34110
12,5	3x 77,2	17,4	250	80	283	CMA34112
Rated AC voltage Urms = 440 VAC, f_n = 50Hz, Delta Connection, with internal discharge resistor⁽¹⁾						
5	3x 27,4	6,6	250	80	283	CMA34405
10	3x 54,8	13,1	250	80	283	CMA34410
12,5	3x 68,6	16,4	250	80	283	CMA34412
15	3x 82,0	19,7	250	80	283	CMA34415
Rated AC voltage Urms = 480 VAC, f_n = 50Hz, Delta Connection, with internal discharge resistor⁽¹⁾						
5	3x 23,0	6,0	250	80	283	CMA34805
10	3x 46	12,0	250	80	283	CMA34810
12,5	3x 57,6	15,0	250	80	283	CMA34812
15	3x 69,1	18,0	250	80	283	CMA34815
Rated AC voltage Urms = 525 VAC, f_n = 50Hz, Delta Connection, with internal discharge resistor⁽¹⁾						
5	3x 19,2	5,5	250	80	283	CMA35205
10	3x 38,5	11,0	250	80	283	CMA35210
15	3x 58	16,6	250	80	283	CMA35215

Remarks:

1) Capacitance, voltage and frequency standard value, other values on request by small batches.

For more information contact us

